

MS1633 FocusBT

Wireless Area-Imaging Scanner

Honeywell's MS1633 FocusBT® is the hand-held area-imaging scanner that surpasses all wireless area-imaging scanners by combining Bluetooth® wireless technology with aggressive scan performance.

Perfect for solving retail and supply-chain management applications, this omnidirectional scanner combines the freedom of Bluetooth V1.2 mobility with many qualities already found in the popular MS1690 Focus®. The MS1633 FocusBT is also ideal for solving healthcare data-capture applications.

Regardless of orientation, FocusBT decodes all standard bar codes in a single flash, including 1D, 2D, GSI DataBar™, PDF417, microPDF, EAN/UCC Composite, Matrix and Postal Codes.

FocusBT features Honeywell's patented RangeGate® technology. With RangeGate, FocusBT scans and stores hundreds of bar codes when outside host system communication range. When the connection is re-established, the stored scans are automatically downloaded to the host.

For image-capture applications, FocusBT combines a high-resolution CMOS sensor with a powerful processor which enables a wide array of outputs.

In addition to automatic infrared object detection, FocusBT comes equipped with several power-save modes and two rechargeable lithium-ion batteries. Each battery provides 8 hours of scanning or approximately 4,800 scans per charge.

For more information on the MS1633 FocusBT wireless area-imaging scanner, please visit www.honeywell.com/aidc



Features

- **Omnidirectional Scanning:** Eliminates need to orientate scanner to bar code
- **TotalFreedom™:** Expands scanner functionality by allowing image processing, decoding and formatting plug-ins to be loaded directly to the scanner instead of the host system
- **Removable Li-ion Battery Pack:** Easily remove and replace battery packs without using tools
- **Mobile Phone Reading:** Excels at scanning coupons and tickets directly from the screen of a mobile device
- **Flexible Licensing Solution:** Meets diverse scanning requirements by offering models with limited decoding capabilities—purchase decoding licenses to enable additional functionality as the need arises
- **PowerSave Modes/PowerSwitch:** Conserves battery life and extends uptime
- **CodeSelect™:** Scans up to 7 bar codes in a single flash and outputs data in any predetermined order
- **Motion Tolerance:** Offers aggressive scanning of bar codes passing by the window in presentation mode

MS1633 FocusBT Technical Specifications

Operational

Light Source	Visible Red LED 645 nm ± 7.5 nm
Visual Indicators	Blue = ready to scan, White = good read; Yellow = automatic scanning; Battery Indicator: Blue = unit powered
Host System Interfaces	USB, RS232, Keyboard Wedge, IBM 46xx (RS485)

Wireless

Radio/Range	2.4 to 2.5 GHz (ISM Band) Frequency - Hopping Bluetooth v1.2; Class 2: 10 m (33') line of sight
Data Rate (Transmission Rate)	1 Mbit/s (721 Kbit/s)
Battery	2300 mAh Li-ion
Number of Scans	up to 4800 scans per charge
Expected Hours of Operation	8 hours
Expected Charge Time	6 hours

Mechanical/Electrical

	Scanner	Charger
Dimensions (LxWxH)	183 mm x 79 mm x 124.5 mm (7.2" x 3.1" x 4.9")	90 mm x 65 mm x 30 mm (3.5" x 2.5" x 1.2")
Weight	290 g (10.2 oz)	85 g (3 oz)
Charging Power (typical)		6.0 W (1.2 A @ 5 V)
Non-Charging Power (typical)		150 mW (30 mA @ 5 V)
DC Transformers	Internal battery	Class 2: 5 VDC @ 2 A
LED Class	Class 1: IEC60825-1, EN60825-1	
EMC	FCC Part 15, ICES-003, EN55022 Class B	

Environmental

Operating Temperature	0°C to 40°C (32°F to 104°F)
Storage Temperature	-20°C to 50°C (-4°F to 120°F)
Humidity	0% to 95% relative humidity, non-condensing
Drop	Designed to withstand 1.5 m (5') drops
Environmental Sealing	Sealed to resist airborne particulate contaminants
Light Levels	100,000 Lux (9,290 foot-candles)

Scan Performance

Scan Pattern	Area Image (1280 x 512 pixel array)
Motion Tolerance	47 cm/s (18 in/s) with 13 mil UPC at optimal focus
Scan Angle	Horizontal: 50°; Vertical: 20°
Print Contrast	20% minimum reflectance difference
Pitch, Skew	75°, 75°
Decode Capabilities	Reads standard 1D, PDF, 2D, Postal and OCR symbologies. Visit www.honeywell.com/aidc/symbologies for details. *Note: Decode capabilities dependent on kit configuration
Warranty	2 year factory warranty (Note: 1 year warranty for battery)



For more information:

www.honeywell.com/aidc

Honeywell Security & Data Collection

Honeywell Scanning & Mobility
90 Coles Road
Blackwood, NJ 08012
856.228.8100
www.honeywell.com

Typical Performance*	
Narrow Width	Depth of Field
5.2 mil (1D)	51 mm - 108 mm (2.0" - 4.3")
7.5 mil (1D)	32 mm - 184 mm (1.3" - 7.3")
13 mil (1D)	0 mm - 330 mm (0" - 13.0")
10 mil (PDF)	0 mm - 330 mm (0" - 13.0")
15 mil (PDF)	0 mm - 432 mm (0" - 17.0")
*Resolution: 1D: 5 mil (0.127 mm) 2D: 7.5 mil (0.19 mm)	
*Performance may be impacted by bar code quality and environmental conditions	

Honeywell