

Highlights

- Special ceramic substrate for super stable performance
- Can be embedded in the use of metal
- Ultra-miniature design of the tag can be applied at the size of the place has special needs
- Several patent technologies

Hummingbird IV

Applications

- Small asset Management
- Firearms Administration



We Provide Reliable RFID Products and Satisfactory Service

General Information

Product number	C016-15IMC
Tag type	Passive, Read/Write
Frequency range	902 ~ 928MHz

RF Specifications

IC	Impinj MONZA2
IC protocol	EPC Class-1 Gen2
Read range	Handheld reader: over 0.8m (2.6ft) Fixed reader: over 1.8m (5.9ft)
EPC size	96 Bits

Physical Specifications

Operating temperature	-30°C ~ 85°C (-22°F ~ 185°F)
Tag application temperature	-40°C ~ 150°C (-40°F ~ 302°F)
Case application temperature	-40°C ~ 80°C (-40°F ~ 176°F)
Mass	2g (0.07 oz)
Dimensions	Φ21 x 5 mm (Φ0.83 x 0.2 in)
Attachment	3M 9609 self adhesive
Color	Customizable



C016-15IMC

- Customers for mass-production may choose chips and case color based on actual needs.
- Providing products with relevant frequencies according to different countries or regions.