

Lowest cost per foot

Highest cost per foot

	<b>Z-Perform™ 1000D 2.4 mil Receipt</b>	<b>Z-Select™ 3000D 2.3 mil Receipt</b>	<b>Z-Perform 1000D 3.5 mil Receipt</b>	<b>Z-Select™ 4000D 3.2 mil Receipt</b>	<b>8000D High-Temp 2.3 mil Receipt</b>	<b>PolyPro™ 4000D 3.8 mil Receipt</b>
	<b>Premium:</b> Standard, premium paper—excellent quality, low cost	<b>Enhanced resistance:</b> Enhanced paper—long-life durability and improved resistance	<b>Heavy duty:</b> Premium thicker paper—improved durability and feel	<b>Exceptional resistance:</b> Thicker topcoated paper—exceptional longlife durability and resistance	<b>Heat resistant:</b> Premium thicker top-coated paper—withstands high temperatures	<b>Waterproof &amp; tearproof:</b> Thicker, topcoated, synthetic, waterproof material and tearproof
<b>Material</b>	Paper	Paper	Paper	Paper	Paper	Polypropylene
<b>Topcoated</b>	No	No	No	Yes	Yes	Yes
<b>Thickness</b>	2.4 mil	2.3 mil	3.5 mil	3.2 mil	3.2 mil	3.8 mil
<b>Archivability</b>	10 years*	25 years*	10 years*	25 years*	20 years*	10 years*
<b>Sensitivity</b>	Medium	High	High	High	N/A	High
<b>Moisture Resistance</b>	No	Yes-Limited**	No	Yes-Limited**	Yes-Limited**	Yes
<b>Chemical Resistance</b>	No	Yes-Limited	No	Yes-Limited	Yes-Limited	Yes-Limited
<b>Scratch Resistance</b>	No	No	No	No	Yes	Yes
<b>Service Temperature</b>	-40° F to 140° F (-40° C to 60° C)	-40° F to 140° F (-40° C to 60° C)	-40° F to 140° F (-40° C to 60° C)	-40° F to 140° F (-40° C to 60° C)	-40° F to 194° F (-40° C to 90° C)	-40° F to 140° F (-40° C to 60° C)
<b>Outdoor Applications</b>	No	No	No	No	Yes	Yes
	* The thermal image will remain legible for the archival life provided the image is fully developed on the recommended thermal printer and the document is stored with compatible materials under proper storage conditions. ** These paper products have moisture resistant features that combat humidity and minimal exposure to water.					